ICE600TTWRS

6.5" WEATHER RESISTANT STEREO IN-CEILING SPEAKER

150W • 8Ω • 48Hz - 20kHz • 89 dB



Ordering

Model ICE600TTWRS • Sold as a single stereo speaker • Paintable grille • 10-year warranty

The OSD Audio ICE600TTWRS plays left and right channels through one 6.5" weather resistant speaker, made for bathrooms, covered patios and small rooms that only have space for one speaker.

Stereo From One Speaker

Dual voice coil design plays both left and right channels through a single 6.5 inch woofer, ideal for bathrooms, closets, hallways and small rooms.

Dual Tweeters

Two 1 inch polycarbonate dome tweeters, one per channel, plus a polypropylene woofer deliver clear, full sound from 48Hz to 20kHz with 150 watts of power handling.

Built for Moisture

Santoprene surround resists heat, cold and humidity without hardening or cracking; the rust-resistant aluminum grille handles bathrooms, laundry rooms, kitchens and covered patios.

Simple Wiring

Connect the left channel to one set of terminals and the right channel to the other; 89 dB sensitivity and 8 ohm impedance per channel work with most stereo amplifiers and receivers.

Check the Fit

Needs a 7.95" cutout and 4.33" of clearance above the ceiling; the paintable grille is 9.06" across. Dog ear clamps, no brackets needed.

Specifications

Type	6.5" weather resistant dual voice coil ceiling speaker
Woofer	6.5" polypropylene cone, Santoprene surround
Tweeters	Dual 1" polycarbonate dome
Terminals	Spring loaded
Frequency Response	48Hz - 20kHz
Power Handling	150W
Sensitivity	89 dB

Impedance	8 Ohms
Outer Diameter	9.06"
Mounting Depth	4.33"
Cutout Diameter	7.95"
Sold As	Single
Warranty	10 Years